



R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

Specification

NYTAL® 200

August 30, 2001

RTV Product Code: **30905**
Composition: Hydrous calcium magnesium silicate mineral mixture
Physical State: White powder

	<u>Specification</u>	<u>Test Method</u>
*Color in Oil	55 minimum	T-950
*Consistency, KU	67-71	T-951
*Fineness, retained on 325 mesh	2.5 maximum	T-944

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 25°C	2.85 Mg/m ³
Hegman Fineness, 3 lbs/gal	1
Moisture Content	0.6%
Oil Absorption, Rub-out	23
pH, 10% Slurry	9.4
Volume Displacement	23.7 lbs/gal
Wratten Brightness	90

*Certified Property

Uses - Interior wall paints, exterior house paints, primers, maintenance paints and traffic paints. Filler for NR, synthetic rubbers, polyolefins and other polymers in specialized applications.

Standard Container – 50 pound paper bag