



R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

Specification

NYTAL® 300H

May 13, 1998

RTV Product Code: **31110**
Composition: Hydrous calcium magnesium silicate mineral mixture
Physical State: White powder

	<u>Specification</u>	<u>Test Method</u>
*Color in Oil	55 minimum	T-950
*Consistency, KU	86 - 90	T-951
*Fineness, retained on 325 mesh	0.1% maximum	T-944
*Hegman Fineness, 3 lbs/gal	3.5 minimum	T-953

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 25°C	2.85 Mg/m ³
Moisture Content	0.6%
Oil Absorption, Rub-out	39
pH, 10% Slurry	9.5
Volume Displacement	23.7 lbs/gal
Wratten Brightness	88

Conforms to ASTM D-605; MIL-P-15172A, Type A; 52-MA-523b, Type II

*Certified Property

Uses - For use in both solvent-thinned and water-thinned coatings for interior wall paints, exterior house paints, maintenance paints and traffic paints.

Standard Container - 50 pound paper bag