



R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

Specification

NYTAL® 3300

August 30, 2001

RTV Product Code: **31320**
Composition: Hydrous calcium magnesium silicate mineral mixture
Physical State: White powder

	<u>Specification</u>	<u>Test Method</u>
*Color in Oil	55 minimum	T-950
*Consistency, KU	58-68	T-1012
*Fineness, retained on 325 mesh	0.1% maximum	T-944
*Hegman Fineness, 3 lbs/gal	3.5 minimum	T-1011

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 25°C	2.85 Mg/m ³
Moisture Content	0.6%
Oil Absorption, Rub-Out	24
pH, 10% Slurry	9.5
G.E. Brightness	90
Volume Displacement	23.7 lbs/gal

Conforms to ASTM D-605; MIL-P-15173A, Type B; 52-MA-523b, Type I

*Certified Property

Uses - NYTAL 3300 is low oil absorption filler of medium coarseness. Used in interior wall paints, exterior house paints, primers, maintenance paints and traffic paints.

Standard Container - 50 pound paper bag