




Material Safety Data Sheet

minusa

Section I. Chemical Product and Company Identification

Product Name/ Trade Name	VANTALC® F2003	Code	69644
Supplier	R. T. VANDERBILT COMPANY, INCORPORATED 30 WINFIELD STREET NORWALK, CT 06855	CAS#	See Section II
		In case of Emergency	(203) 853-1400
Synonym	Industrial talc	Protective Clothing	
Chemical name	Hydrous magnesium silicate mineral.		
Chemical Family	Phyllosilicates (structural)		
Manufacturer	R. T. Vanderbilt Company, Inc. 30 Winfield Street Norwalk, CT 06855	Material Uses	Additive in paints and ceramics

Section II. Hazardous Ingredients

Name	CAS #	% by Weight	TLV/PEL
talc	14807-96-6	98-100	TWA 2 mg/m ³ from respirable fraction (ACGIH) See Section XVI (OSHA)
Total Product			As above.

Section III. Hazards Identification

Emergency Overview	Not an acute hazard. May cause mechanical eye or skin irritation in high concentrations. As with all mineral spills, minimize dusting during clean-up. Do not breathe dust. Prolonged inhalation may cause lung injury. Product can become slippery when wet.
Target Organs	Pulmonary System (chronic risk).

Section IV. First Aid Measures

Eye Contact	Flush with plenty of flowing water. Get medical attention if irritation persists.
Skin Contact	Wash off with water.
Inhalation	Allow the victim to rest in a well ventilated area if high concentration is inhaled and mechanical irritation or discomfort occurs. Seek medical attention if irritation persists.
Ingestion	Unlikely to be toxic by ingestion.

Section V. Fire and Explosion Data

Flammability of the Product	Non-flammable.
Autoignition Temperature	Not applicable.
Flash Point	Not applicable.
Flammable Limits	Not applicable.
Products of Combustion	Not applicable.
Fire Hazards in Presence of Various Substances	Not considered to be flammable according to our database.
Explosion Hazards in Presence of Various Substances	None.
Fire Fighting Media and Instructions	Product will not burn, use appropriate extinguishing media for surrounding fires.
Special Remarks on Fire Hazards	No additional remark.
Special Remarks on Explosion Hazards	No additional remark.

Section VI. Accidental Release Measures

Small Spill	Use a vacuum to clean up spillage. If appropriate, use gentle water spray to wet down and minimize dust generation. Place in a sealed container.
Large Spill	Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Avoid excessive dust generation. Use respiratory protection in high dust conditions.

Section VII. Handling and Storage

Handling and Storage Procedures	No special storage considerations. Handle in ways which minimize dust generation.
--	---

Section VIII. Exposure Controls, Personal Protection

Engineering Controls	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If local exhaust ventilation is used, a capture velocity of 150-200 fpm is recommended.
Personal Protection	Safety glasses. Any NIOSH approved filler dust respirator. No special skin protection required. Wash skin if mechanical irritation is experienced.

Section IX. Physical and Chemical Properties

Appearance	White powder
Molecular Weight	Not available.
pH	Not available
Melting/ Sublimation Point	Not available.
Specific Gravity	2.8 (Water = 1)

Continued on Next Page

Volatility	Non-volatile.
Odor	None
Solubility	Insoluble in cold water.

Section X. Stability and Reactivity Data

Stability	The product is stable.
Instability Temperature	Not applicable
Conditions of Instability	None known
Incompatibility with Various Substances	Non reactive.
Corrosivity	No specific information is available in our database regarding the corrosivity of this product in presence of various materials.

Section XI. Toxicological Information

Routes of Entry	Inhalation. Ingestion.
Acute Effects	
Eye Contact	Not a primary eye irritant. May cause mechanical irritation,
Skin Contact	Mechanical skin irritation is possible but unlikely. Not absorbed through skin. Possible granuloma formation in open wounds (requires repeated, massive applications).
Sensitization	Not a sensitizer.
Ingestion	Not an ingestion hazard.
Inhalation	Inhalation of high concentrations may cause mechanical irritation and discomfort. Repeated exposure may cause chronic effects.
Remarks	No additional remark.
Chronic Effects	CARCINOGENIC EFFECTS See remarks. MUTAGENIC EFFECTS None known. TERATOGENIC EFFECTS None known. DEVELOPMENTAL TOXICITY None known.
Remarks	TALC: Prolonged exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or of the covering of the lungs (pleural thickening). Pneumoconiosis may produce symptoms of cough or shortness of breath. Pleural thickening usually produces no symptoms. Conditions can be determined by chest radiographic examination and pulmonary function test (FEV and FVC). Bronchial irritation may cause sputum production. Excessive exposure to any dust may aggravate pre-existing respiratory conditions.

Section XII. Ecological Information

Ecotoxicity None known.

BOD5 and COD Not available.

Products of Biodegradation None known.

Toxicity of the Products of Biodegradation None known.

Special Remarks on the Products of Biodegradation No additional remark.

Section XIII. Disposal Considerations

Waste Information Not a RCRA hazardous waste. Dispose of according to state or local regulations.

Section XIV. Transport Information

DOT Not a DOT controlled material (United States).



Not applicable.

Maritime transportation Not available.

Section XV. Regulatory Information

TSCA Listed.

Federal and State Regulations TSCA 8(b) inventory: VANTALC® F2003


OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Hazardous Material Information System (U.S.A.)

Health Hazard	*	1
Fire Hazard		0
Reactivity		0
Personal Protection		E

* Chronic Potential

National Fire Protection Association (U.S.A.)



**Protective Clothing
(Pictograms)****Section XVI. Other Information**

References Not available.

Other Special Considerations Talc PEL: The current OSHA PEL remains 20 mppfc. Due to antiquated particle counting technique, the gravimetric (ACGIH) limit is recommended.

Validated by Sue Kelly on 3/1/2005.

Previous Validation Date 3/1/2005.

Verified by Sue Kelly.

Printed 3/11/2005.

Information Contact John Kelse (203) 853-1400 ext. 217
Corporate Risk Management

Notice to Reader

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.