



Product Data Sheet

Revision Date: 01/04

SYLVATAC[®] RE 5 (Formerly SYLVATAC[®] RE54)

Liquid Rosin Ester

SYLVATAC RE 5 RESIN is a liquid rosin ester tackifier designed for applications requiring low odor and excellent stability. **SYLVATAC RE 5 RESIN'S** high acid number provides improved specific adhesion relative to alternative liquid resins.

SPECIFICATIONS

Softening Point, Ring & Ball, °C	Liquid
Acid Number	60 - 66
Color, Solid, Gardner	10 Maximum

TYPICAL PROPERTIES

Softening Point, Ring & Ball, °C	Liquid
Color, Solid, Gardner	7
Acid Number	62
Pounds per Gallon, 25°C	8.5

Recommended Uses:

SYLVATAC RE 5 RESIN is recommended as an adhesive tackifier where the specific adhesion and wetting performance of a premium rosin ester is required along with excellent stability. Recommended uses include packaging, bookbinding, pressure sensitive and other adhesive applications as well as sealants, coatings and wax-based products.

FDA Status:

SYLVATAC RE 5 RESIN meets the requirements of the Code of Federal Regulations, Title 21, under the following section:

DOT Shipping Classification:

Non-hazardous.

Packaging:

Viscous liquid in 55-gallon steel drums (420 lbs. net) or molten bulk.

Shipping Point:

Port St. Joe, Florida

Safety Information:

Refer to Material Safety Data Sheet #6759



Technical Service: Savannah, GA (912) 238-6556

Sales Service: Jacksonville, FL - (800) 733-1374

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.