


IF YOU...



MIX IT. FILL IT. PACK IT. SHIP IT.

WE HAVE A PRODUCT FOR YOU



30 Gallon Hazardous Drum Heater w/
Preset Temperature, 122°F - IntelHeat™

Product Category: Drum Heaters

Part #	19BHH3
Capacity	30 gal.
Color	Black
Dimensions	55" - 65" Adjustable Circumference, 14.8"H
Material	Nylon
Case Pack	1 ea.
Pallet Pack	24 ea. (24 Cases)

The
CARYCOMPANY
Est. 1895

1195 W. Fullerton Ave. | Addison, IL 60101 | T: 630.629.6600 | F: 630.629.3690 | TheCaryCompany.com

InteliHeat® Class I Division 2 30-gallon Heating Jacket (HJNA/C/D2)

Our InteliHeat® CID2 30-gallon Heating Jacket certified for use in Class I Division 2 Classified Hazardous Locations is ideal for gentle heating and freeze protection depending on the severity of environmental conditions.

- Ideal for gently heating, will typically maintain materials around 95°F(35°C).
- Fixed internal thermostat: 122°F(50°C).
- Polyurethane coated black nylon used on both sides of the jacket (inner and outer) to ensure maximum wear resistance.
- High grade thermal insulation to reduce heat loss and increase efficiency while providing protection for the operator.
- Fitted with adjustable retaining straps and quick release buckles.
- Flexible - conforms to the container wall providing optimal thermal coupling
- Delivers heat over a large surface area, minimizing the possibilities of damaging the product.
- Fit and forget, built to last - no regular maintenance required.
- Safe to use 24/7.
- 16 ft. (5m) premium oil, water, and abrasion resistant SOOW power cable
- Double insulated product
- Ambient temperature: -40°F to +104°F (-40°C to +40°C)
- ETL approved to UL and CSA standards. Suitable for Class I Division 2 and Class I Zone 2 locations
- Waterproof and custom sizes available.

Hazardous Location Marking:

Class I Division 2, Groups ABCD, T3. Class I Zone 2, IIC, T3.

Class II Division 2, Groups EFG, T3. Class II Zone 22, IIIB, T3. Class III Division 1 and 2, T3

T4 rating available on request

To fit container: 30 Gallon / 100 Liter

Thermostat: Fixed 50°C / Fixed 122°F

Size: Circumference 55" – 65" / Height 14.8" (1400 – 1650mm / 375mm)

120 Volts

450 Watts