

# IF YOU...



MIX IT. FILL IT. PACK IT. SHIP IT.

# WE HAVE A PRODUCT FOR YOU



Part #	30W10E
Capacity	10 Liter, 2.5 gal.
Overflow Capacity	2.9 gal. (10.97 L)
Color	Natural
Material	LDPE
Dimensions	9.3" x 9.3" x 9.3"
Neck Finish	38-400
Neck Width	38mm
FDA Approved	Yes
Case Pack	100 ea.
Pallet Pack	1,200 ea. (12 Bundles)

# CUBITAINER® COMBINATION PACKAGE

Issue Date: Dec. 15, 1994

Specification No. CUB4892  
2.5 Gallon/10 Liter, 38mm  
CUBITAINER® Insert



Supplied By: **The Cary Company**

Ph: 630-629-6600

www.thecarycompany.com

**SCOPE:**

This specification covers the description of the 2.5 gallon/10 liter, 38mm CUBITAINER® insert.

**DESCRIPTION:**

The 2.5 gallon/10 liter, 38mm CUBITAINER® insert is a linear low density polyethylene blend cubically shaped liner, designed for use with a corrugated fibreboard overpack. The insert is manufactured by the CUBITAINER® process with the seam located along the diagonal periphery.

A reversible well is molded in the top face of the insert to accommodate a mechanically bonded 38mm closure designed to accept a 38-400 screwcap.

**MATERIAL:**

Linear low density polyethylene blend conforming to the following:

Density.....	0.910 - 0.925 gms/cc
Melt Index.....	2.6 maximum
Tensile Strength.....	1500 lbs/in <sup>2</sup> minimum
Percent Elongation.....	400% minimum

Regrind of the same material may be utilized in processing. This material conforms to FDA Regulation, 177.1520 which permits the use of polyethylene in articles that contact food.

**DIMENSIONAL DATA:**

Minimum Wall Thickness.....	0.010"
Average Wall Thickness.....	0.020"
Nominal Weight.....	135 grams*

**38MM THREADED OPENING:**

Injection molded, high density polyethylene with neck sealant.



Supplied By: **The Cary Company**

Ph: 630-629-6600

www.thecarycompany.com

**ASSEMBLY:**

The CUBITAINER® insert may be purchased knocked down in bulk quantities or set up in a corrugated fibreboard carton as a composite CUBITAINER® container. If the insert is purchased in bulk, the customer may supply his own carton or purchase the cartons knocked down from Hedwin. Upon customer request, Hedwin will provide technical specifications concerning the cartons and the equipment necessary for assembling CUBITAINER® composites.

**PACKING:**

Units are shipped knocked down, 36 per box.

\*This weight is established on the basis of currently available processing technology at the date of publication of this specification. Hedwin reserves the right to revise this weight specification while holding other parameters of thickness and performance constant.

Specification current at time of issue.