

# Part#: 37BC10



Part#	Description	Dimensions	Weight	Capacity
37BC10	Ultra Stake Wall Containment Berm	15'x66'x1'	464 lbs	7405 Gallons

Photo does not depict actual size.



Supplied By: **The Cary Company**  
Ph: 630-629-6600  
[www.thecarycompany.com](http://www.thecarycompany.com)

## COPOLYMER-2000 - SPECIFICATIONS

Reinforced	Standard	Metric
Base Fabric Type	Polyester	
Base Fabric Weight (nominal)	3.0 oz/yd <sup>2</sup>	102 g/m <sup>2</sup>
Finished Coated Weight ASTM D751	28.0 ± 2 oz/yd <sup>2</sup>	950 ± 70 g/m <sup>2</sup>
Thickness ASTM D751	30 mils nominal	0.76 mm nominal
Trapezoid Tear ASTM D4533	30/30 lb <sub>r</sub> nominal	133/133 N nominal
Grab Tensile ASTM D751 Grab Method	250/200 lb <sub>r</sub> min.	1112/890 N min.
Hydrostatic Resistance ASTM D751, Procedure A	300 psi min.	2.06 MPa min.
Adhesion ASTM D751 Dielectric Seam	10 lb <sub>r</sub> /in min.	9.0 daN/5 cm min.
Cold Crack ASTM D2136 1/8 in mandrel, 4 hr.	Pass @ -25° F	Pass @ -32° C
Puncture Resistance ASTM D4833	50 lb <sub>r</sub> typical	225 N typical
Dead Load ASTM D751	2 in seam, 4 hr, 1 in strip 100 lb <sub>r</sub> @ 70° F 50 lb <sub>r</sub> @ 160° F	5 cm seam, 4 hr, 2.5 cm strip 445 N @ 21° C 220 N @ 70° C

We believe this information is the best currently available on the subject. We offer it as a suggestion in any appropriate experimentation you may care to undertake. It is subject to revision as additional knowledge and experience are gained. We make no guarantee of results and assume no obligation or liability whatsoever in connection with this information. In case of conflict between standard and metric specifications, standard shall apply.



PH 630-629-6600 - FX 630-629-3690  
 1195 W. FULLERTON AVE. - ADDISON, IL 60101  
 WWW.THECARYCOMPANY.COM