

Part#: 37BC19



Part#	Description	Dimensions	Weight	Capacity
37BC19	Ultra Compact Containment Berm	10'x10'x1'	72 lbs	748 Gallons

Photo does not depict actual size.



Supplied By: **The Cary Company**
Ph: 630-629-6600
www.thecarycompany.com

COPOLYMER-2000 - SPECIFICATIONS

Reinforced	Standard	Metric
Base Fabric Type	Polyester	
Base Fabric Weight (nominal)	3.0 oz/yd ²	102 g/m ²
Finished Coated Weight ASTM D751	28.0 ± 2 oz/yd ²	950 ± 70 g/m ²
Thickness ASTM D751	30 mils nominal	0.76 mm nominal
Trapezoid Tear ASTM D4533	30/30 lb _r nominal	133/133 N nominal
Grab Tensile ASTM D751 Grab Method	250/200 lb _r min.	1112/890 N min.
Hydrostatic Resistance ASTM D751, Procedure A	300 psi min.	2.06 MPa min.
Adhesion ASTM D751 Dielectric Seam	10 lb _r /in min.	9.0 daN/5 cm min.
Cold Crack ASTM D2136 1/8 in mandrel, 4 hr.	Pass @ -25° F	Pass @ -32° C
Puncture Resistance ASTM D4833	50 lb _r typical	225 N typical
Dead Load ASTM D751	2 in seam, 4 hr, 1 in strip 100 lb _r @ 70° F 50 lb _r @ 160° F	5 cm seam, 4 hr, 2.5 cm strip 445 N @ 21° C 220 N @ 70° C

We believe this information is the best currently available on the subject. We offer it as a suggestion in any appropriate experimentation you may care to undertake. It is subject to revision as additional knowledge and experience are gained. We make no guarantee of results and assume no obligation or liability whatsoever in connection with this information. In case of conflict between standard and metric specifications, standard shall apply.



PH 630-629-6600 - FX 630-629-3690
 1195 W. FULLERTON AVE. - ADDISON, IL 60101
 WWW.THECARYCOMPANY.COM

SPECIFICATIONS

KEY FEATURES AND BENEFITS

- Compact, lightweight, portable design - no inflation required.
- Smaller sizes provide total containment of drums, tanks, generators, compressors and other equipment prone to leaks and spills.
- Standard material of construction is Copolymer 2000™.

SIDEWALLS:

- Attached aluminum struts insert into sleeves along the side-wall.
- Sidewalls must be put up or taken down manually when driving vehicle or equipment into Berm.

COMPLIANCE:

- EPA 40 CFR 264.175 Containment of Containers Containing Free Liquid.
- SPCC - Spill Prevention, Control and Countermeasure Act



STANDARD SIZES AVAILABLE

	Size	Capacity	Weight
Part# 8609	4' x 6' x 1'(1.2 m x 1.8 m x .3 m)	179 gallons (678 L)	29 lbs. (13 kg)
Part# 8610	6' x 6' x 1'(1.8 m x 1.8 m x .3 m)	269 gallons (1,018 L)	35 lbs. (16 kg)
Part# 8611	10' x 10' x 1'(3 m x 3 m x .3 m)	748 gallons (2,831 L)	63 lbs. (29 kg)
Part# 8612	12' x 60' x 1' (3.7 m x 18.3 m x .3 m)	5,385 gallons (20,382 L)	309 lbs. (140 kg)
Part# 8613	15' x 50' x 1'(4.6 m x 15.2 m x .3 m)	5,610 gallons (21,234 L)	278 lbs. (126.5 kg)
Part# 8614	15' x 66' x 1'(4.6 m x 20.1 m x .3 m)	7,405 gallons (28,028 L)	357 lbs. (162 kg)
Custom Sizes Available.			

MATERIAL SPECIFICATIONS (Specs shown are for Copolymer-2000. Other materials available.)

Reinforced	Standard	Metric
Base Fabric Type	Polyester	
Base Fabric Weight (nominal)	3.0 oz/yd ²	102 g/m ²
Finished Coated Weight - ASTM D751	28.0 ± 2 oz/yd ²	950 ± 70 g/m ²
Thickness - ASTM D751	30 mils nominal	0.76 mm nominal
Trapezoid Tear - ASTM D4533	30/30 lb _f nominal	133/133 N nominal
Grab Tensile - ASTM D751 Grab Method	250/200 lb _f min.	1112/890 N min.
Hydrostatic Resistance - ASTM D751, Procedure A	300 psi min.	2.06 MPa min.
Adhesion - ASTM D751 Dielectric Seam	10 lb _f /in min.	9.0 daN/5 cm min.
Cold Crack - ASTM D2136 1/8 in mandrel, 4 hr.	Pass @ -25° F	Pass @ -32° C
Puncture Resistance - ASTM D4833	50 lb _f typical	225 N typical
Dead Load - ASTM D751	2 in seam, 4 hr, 1 in strip 100 lb _f @ 70° F 50 lb _f @ 160° F	5 cm seam, 4 hr, 2.5 cm strip 445 N @ 21° C 220 N @ 70° C



PH 630-629-6600 - FX 630-629-3690
 1195 W. FULLERTON AVE. - ADDISON, IL 60101
 WWW.THECARYCOMPANY.COM