

Part#: 37BC24



| Part# | Description | Dimensions | Weight | Capacity |
|--------|-----------------------------------|------------|--------|-------------|
| 37BC24 | Rapid Rise Model Containment Berm | 6'x6'x1' | 35 lbs | 269 Gallons |

Photo does not depict actual size.



Supplied By: **The Cary Company**
Ph: 630-629-6600
www.thecarycompany.com

SPECIFICATIONS

KEY FEATURES AND BENEFITS

- Sidewalls remain down during normal operations, loading and unloading. Vehicles and equipment can drive in and out with no set-up or take-down required
- In the case of a spill, the foam ring around the top perimeter of the Containment Berm rises with the level of spilled liquid.
- Standard material of construction is Copolymer 2000™.



SIDEWALLS:

- Lay flat unless spill occurs - foam ring will rise with liquid level.
- Eliminates tripping hazards.
- No set-up required once Berm has been positioned in the field.

COMPLIANCE:

- EPA 40 CFR 264.175 Containment of Containers Containing Free Liquid.
- SPCC - Spill Prevention, Control and Countermeasure Act



STANDARD SIZES AVAILABLE

| | Size | Capacity | Weight |
|--------------------------------|---------------------------------------|--------------------------|---------------------|
| Part# 8430 | 4' x 6' x 1'(1.2 m x 1.8 m x .3 m) | 179 gallons (678 L) | 29 lbs. (13 kg) |
| Part# 8431 | 6' x 6' x 1'(1.8 m x 1.8 m x .3 m) | 269 gallons (1,018 L) | 35 lbs. (16 kg) |
| Part# 8432 | 10' x 10' x 1'(3 m x 3 m x .3 m) | 748 gallons (2,831 L) | 63 lbs. (29 kg) |
| Part# 8437 | 12' x 26' x 1' (3.7 m x 7.9 m x .3 m) | 2,333 gallons (8,831 L) | 149 lbs. (67.5 kg) |
| Part# 8433 | 15' x 50' x 1'(4.6 m x 15.2 m x .3 m) | 5,610 gallons (21,234 L) | 278 lbs. (126.5 kg) |
| Part# 8434 | 15' x 66' x 1'(4.6 m x 20.1 m x .3 m) | 7,405 gallons (28,028 L) | 357 lbs. (162 kg) |
| Custom Sizes Available. | | | |

MATERIAL SPECIFICATIONS (Specs shown are for Copolymer-2000. Other materials available.)

| Reinforced | Standard | Metric |
|---|---|---|
| Base Fabric Type | Polyester | |
| Base Fabric Weight (nominal) | 3.0 oz/yd ² | 102 g/m ² |
| Finished Coated Weight - ASTM D751 | 28.0 ± 2 oz/yd ² | 950 ± 70 g/m ² |
| Thickness - ASTM D751 | 30 mils nominal | 0.76 mm nominal |
| Trapezoid Tear - ASTM D4533 | 30/30 lb _f nominal | 133/133 N nominal |
| Grab Tensile - ASTM D751 Grab Method | 250/200 lb _f min. | 1112/890 N min. |
| Hydrostatic Resistance - ASTM D751, Procedure A | 300 psi min. | 2.06 MPa min. |
| Adhesion - ASTM D751 Dielectric Seam | 10 lb _f /in min. | 9.0 daN/5 cm min. |
| Cold Crack - ASTM D2136 1/8 in mandrel, 4 hr. | Pass @ -25° F | Pass @ -32° C |
| Puncture Resistance - ASTM D4833 | 50 lb _f typical | 225 N typical |
| Dead Load - ASTM D751 | 2 in seam, 4 hr, 1 in strip 100 lb _f @ 70° F 50 lb _f @ 160° F | 5 cm seam, 4 hr, 2.5 cm strip 445 N @ 21° C 220 N @ 70° C |



PH 630-629-6600 - FX 630-629-3690
 1195 W. FULLERTON AVE. - ADDISON, IL 60101
 WWW.THECARYCOMPANY.COM