


IF YOU...



MIX IT. FILL IT. PACK IT. SHIP IT.

WE HAVE A **PRODUCT** FOR YOU



Part #	37BCG7
Color	Black
Duribility	Standard
Dimensions	20"L x 16"W x 18"H up to 32"L x 26"W x 18"H
Model	UltraTech 8930



Ultra-Drain Guards[®]

Specifications

Material Specifications

Properties	ASTM Test	Value
Material: Non-woven, Polypropylene Geotextile		
Grab Tensile	D 4632	205 lbs
Elongation	D 4632	50%
Trapezoid Tear	D 4533	80 lbs
Puncture	D 4833	525 lbs
CBR Puncture	D 6241	600 lbs
Mullen Burst	D 3786	420 psi
Permittivity	D 4491	1.5 sec ⁻¹
A.O.S. (U.S. sieve no.) / Microns	D 4751	80 / 180
UV Stability (strength retained %) 500 hrs	D 4355	70%
Fabric Weight (oz/yd ²) (typical)	D 5261	8 oz/yd ²
Flow (through material)	D 4491	90 gpm/ft ²
Flow (bypass ports gpm) *		770 gpm
Flow (bypass ports cfs) *		1.7 cfs

* Larger bypass flow rate designs are available



Unit Specifications

Model	Oil Capture (Gal)	Sediment Capture (lbs)	Collection Area (dia x depth)	Flow Rate (gpm)	Dimensions
Oil & Sediment ² Part # 9217	.87	40	10" x 18"	500	48" x 36" x 18"
Oil & Sediment ² Part # 9356	1.55	40	10" x 18"	900	60" x 60" x 18"
Oil & Sediment Plus ² Part # 9219	1.38	40	10" x 18"	500	48" x 36" x 18"
Oil & Sediment Plus ² Part # 9358	2.06	40	10" x 18"	900	60" x 60" x 18"
Trash & Debris Part # 9227	----	40	10" x 18"	500	48" x 36" x 18"
Ultimate ³ Part # 9376	1.57	40	10" x 18"	500	48" x 36" x 38"
High Capacity Part # 9393	1.9	300	24" x 24"	1000	60" x 60" x 24"
Adjustable Frame Model Part # 8930	1.26	40	10" x 18"	500	Varies