IF YOU... MIX IT. FILL IT. PACK IT. SHIP IT.

WE HAVE A PRODUCT FOR YOU

24″ x 36″ Curb Style Ultra-Drain Guard®, Reusable Model

Product Category: Drain Guards

Part #	37BRG7
Color	Yellow
Collection Area	36″ Depth
Flow Rate	695 gal/min/sq ft
Sediment Capture	500 lbs.
Duribility	Standard
Dimensions	24″ x 36″ (610 mm x 915 mm)
Model	UltraTech 9330

The CARY COMPANY Est. 1895

1195 W. Fullerton Ave. | Addison, IL 60101 | T: 630.629.6600 | F:630.629.3690 | TheCaryCompany.com

The CARY COMPANY Est. 1895

Ultra-Drain Guard, Reusable Model®

SPECIFICATION SHEET

Material Specifications		
Properties	ASTM Test	Value
Material: Woven Polypropylene Geotextile	----	----
AOS (U.S. Sieve)	D 4751	20 sieve
Permeability	D 4491	.49 cm/ sec
Permittivity	D 4491	.473 sec^{-1}
Flow Rate	D 4491	695 gal/min/ft^2
Mullen Burst	D 3786	542 psi
Puncture	D 4833	104 lbs.
Tensile MD	D 4632	237 lbs.
Tensile CD	D 4632	255 lbs.
Trapezoid Tear	D 4533	115 lbs.

Unit Specifications				
Model	Sediment Capture	Collection Area	Flow Rate	Dimensions
Reusable	500 lbs.	36" Depth	695 gal/min/ft^2	See below

Available Unit Dimensions and Accessories	
Part #	Dimensions
9341	24"x24" (610 mm x 610 mm)
9340	24"x36" (610 mm x 915 mm)
9342	24"x48" (610 mm x 1220 mm)
9332	24"x24", Curb-Style (610mm x 610mm)
9330	24"x36", Curb-Style (610 mm x 915 mm)
9331	24"x48", Curb-Style (610 mm x 1220 mm)