


IF YOU...



MIX IT. FILL IT. PACK IT. SHIP IT.

WE HAVE A PRODUCT FOR YOU

Part #: 56WGB5

Tight Head Plastic Drums

55 Gallon Blue Tight Head Plastic Drum, UN Rated,
2" NPT & 2" Buttress Fittings



The
CARYCOMPANY
Est. 1895

1195 W. Fullerton Ave. | Addison, IL 60101 | T: 630.629.6600 | F: 630.629.3690 |

55 Gallon Tight Head Drum



Technical Data (Nominal)

Regulatory Information: 1H1/Y1.9/150 and 1H1/Y1.4/150 Vented

Capacity: 55 gallons

Assembled Height: 34.75"

Assembled Weight: 21 lbs.

Greatest Outside Dimension: 23.57"

Minimum Wall Thickness: 2.2mm (D.O.T.)

Description

Body Construction: Blow molded with a minimum measurement of 2.2 mm all around the body circumference and along the length of the body.

Material: High Molecular Weight High Density Polyethylene that is FDA compliant.

Color: Blue, Black, Natural, or Custom colors available – minimum quantities apply

Closure systems: 2" buttness and 2" NPS plugs. EPDM gaskets are standard. 2" buttness with 3/4 inch reducer and faucet carrier are available. Additional gasket materials are available. Specialty closure systems and gaskets are available. The following closure combinations give maximum assurance:

- 2" Buttness Plug – Non Vented
- 2" NPS Plug – Non Vented
- 2" Buttness Plug with 3/4" Fine Thread Plug

Exterior Decoration: Every drum offers a large area on the body for the application of labels and sleeves.

Options: Plastic dust covers, tamper resistant and tamper evident snap seals and sealing caps.

Kosher Certified

UN-approved plastic drums are manufactured using state-of-the-art technologies to meet the stringent demands of chemical compatibility with hazardous and non-hazardous products as well as reliability and safety requirements for the U.S. chemical and food service industries. Our list of uses include, but are not limited to, the detergent, lubricant, pharmaceutical and agrochemical industries.

Our 55 gallon tight head drums are extremely strong and compatible with most drum handling devices. In addition, our drums include a bottom handhold for easy use. We are FDA compliant and Kosher certified.



NPS Threaded Plug



Buttness Threaded Plug

SPECIAL NOTES

1. Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking strength.
2. Drums may be stacked 3 high maximum with pallets between drums. Maximum top load on bottom drums not to exceed 2,000 lbs. each. Pallets should be of good quality that provide adequate support for plastic drums.
3. Handle with parrot beak, side grabber, and sling.
4. Recycle symbol, alignment arrows, and bung types are molded on the drum. Lot number is on the bottom.