


# IF YOU...



MIX IT. FILL IT. PACK IT. SHIP IT.

# WE HAVE A **PRODUCT** FOR YOU

Part #67WSC2

Preform Bands

---

## 120mm Clear Preform Plastic Shrink Band For Canister Containers

---



---

The  
**CARY**COMPANY  
Est. 1895

Product Summary - PVC (Polyvinyl chloride) Heat Shrinkable Packaging Film

- Recycling Symbol: 03 PVC
- Recycling Considerations: General re-melting and filtration process can be used.
- Disposal: Should not be burned, generates HDI. General dumping and landfill system compatible. Non-biodegradable.
- Heat Resistance: 70-80° C before deformation
- Cold Resistance: -30° C before brittle/cracking (can be extended to -40° C with additives)
- Fat Resistance: Excellent
- Steam Resistance: Good
- Gas Resistance: Good
- Shrink Ratio: up to 63% of original layflat size
- Food Grade (US FDA Standard) film can be requested for direct-contact food applications.
- Recommended Shrink Temperature: 110-150° C

**SECTION I - PRODUCER**

---

**Product Name:** Solid Seal® PVC Shrinkable Film      **Formula:** NT

**SECTION II - INGREDIENTS**

---

Main Ingredient	Typical Percent	OSHA PEL Gas Fume Dust ppm mg/m <sup>3</sup>	ACGIH TLV Gas Fume Dust ppm mg/m <sup>3</sup>	CAS Numbers
Polyvinyl Chloride resin (Not a Hazardous material, under OSHA Standards)	70-80%	N/D	N/D	N/A

**SECTION III - PHYSICAL DATA**

---

**Melting Range:** 200-250° C    **Vapor Density:** N/A    **Evaporation Rate:** N/A

**Boiling Point:** 310° C    **Vapor Pressure:** N/A    **Specific Gravity:** 1.4kg/dm<sup>3</sup>

**Appearance and Odor:** Clear Plastic Film, with light odor

**Solubility in Water:** Insoluble

Notes: N/D = Not Determined    N/A = Not Applicable

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

---

**Flash Point:** N/A    **LEL:** N/A    **UEL:** N/A

**Extinguishing Media:** Water, Carbon Dioxide, or other standard fire-fighting agents

**Special Fire Fighting Procedures:** Use self-contained breathing apparatus.

Notes: N/D = Not Determined    N/A = Not Applicable