


IF YOU...



MIX IT. FILL IT. PACK IT. SHIP IT.

WE HAVE A PRODUCT FOR YOU

Part #: 77WMAL

Pail Liners

5 Gallon HDPE (15 mil)
Anti-Static Liner for Steel Pails



The
CARYCOMPANY
Est. 1895

1195 W. Fullerton Ave. | Addison, IL 60101 | T: 630.629.6600 | F: 630.629.3690 | TheCaryCompany.com

PAILSAVER™ INSERT FOR STEEL PAILS

PRODUCT DESCRIPTION: The 5HD/AS/22, the anti-stat version of our industry standard 5HD, is a rigid, durable, straight-sided, seamless, vacuum-formed insert for 5-gallon steel pails. This robust insert is molded from FDA-approved high-density polyethylene, which provides better resistance to many solvents, compared to LDPE. A contoured lip snaps over the top bead to prevent leakage between the insert and the pail wall.

Insert Specifications

MATERIAL USED

High-density polyethylene

INSERT DIMENSIONS

Diameter: 11.25" (+0.25"/-0")

Height: 13" (+/-0.125")

Average thickness: 15 mil (+/-10%)

WEIGHT

.25 lbs. (+/-10%)

SIDE-WALL DESIGN

Straight-sided

TEMPERATURE PARAMETERS

High (momentary): 175° (195°)F

Low: -40° F

ANTI-STAT

Standard: NFPA-99

Resistivity rating: 10¹¹ Ω/sq. typical

Packaging Specifications

CARTON WEIGHT

28.5 lbs.

CARTON DIMENSIONS

Length: 23.625"

Width: 23.625"

Height: 27"

QUANTITY/CASE

100

PACKAGING STYLE

Nested

CDF's ANTI-STAT LINERS CONTAIN AN INTERNAL ANTI-STAT AGENT THAT IS INTENDED AS AN AID TO REDUCTION OF STATIC BUILD-UP. THEY ARE NOT DESIGNED AS, AND SHOULD NOT BE USED AS, THE PRIMARY CONTROLLER OF STATIC ELECTRICITY IN A PROCESS. CDF's ANTI-STAT LINERS SHOULD NOT BE USED IN ELECTRO-STATIC COATING SYSTEMS OR OTHER HIGHLY VOLATILE AREAS. PLEASE CONSULT YOUR SAFETY ENGINEER, SAFETY CONSULTANT, OR CDF IF THERE IS ANY QUESTION AS TO APPROPRIATENESS OF USE.

TYPICAL APPLICATIONS: The 5HD/AS/22 is perfect for mixing, pumping and storing all liquids, powders and pastes that can be contained in high-density polyethylene, as well as resist long-term exposure to a wide range of materials.