HOW TO ORDER TOP INLET MODEL 8: SIZE #1 & SIZE #2 FILTER BAG HOUSINGS

HOUSING OPTIONS

Example: OT8-15-2P-1-150-C-B-S-PB-P-D-C

MODEL#
OT8

HOUSING SIZE
15 Inch – 15
30 Inch - 30

PIPE SIZE NPT / FLANGE
2" Female NPT - 2P
2" 150 Class ANSI Flange - 2F

OUTLET STYLE
Bottom - 1
Side Top - 2
90º Elbow - 3
Same Side - 4

PRESSURE RATING
150 PSI (NPT or Flanged) - 150

HOUSING MATERIAL
Carbon Steel - C
304 Stainless Steel - S
316 Stainless Steel - S316

COVER SEAL
Buna N - B
Ehylene Propylene - E
Viton® Fluoroelastomer - V
Teflon® Encapsulated Viton® - TEV[5]
Teflon® (solid white) (6 Bolt Cover) - TSW[5]

ASME CODE STAMP
Code - C
NSF 61 Listed - NSF

DISPLACER
Displacer - D

BASKET, MEDIA SIZE
**No symbol if type b basket was selected*
Perforated Diameters (for Type P Baskets)
1/4, 3/16, 9/64, 3/32, 1/16
Mesh Sizes (for Type M and BM Baskets)
20, 30, 40, 50, 60, 70, 80, 100, 150, 200

BASKET TYPE
Filter Bag Basket, 9/64 Perforations[3] - PB
Strainer Basket, Perforated Metal - P
Filter Bag Basket, Perforated, Mesh Lined[3] - BM
Strainer Basket, Perforated, Mesh Lined - M
Filter Bag Basket , Heavy Wire Mesh[3] - HWM

BASKET SEAL
Seal Required - S

The CARY COMPANY Est. 1895

1195 W. Fullerton Ave. | Addison, IL 60101 | T: 630.629.6600 | F:630.629.3690 | TheCaryCompany.com