

DRUM & PAIL HEATERS

Featuring patented technology, **Powerblanket® Lite** delivers a barrier of uniform directional heat where it's needed most – preventing fluids from freezing and maintaining optimal temperatures. This innovative heat spreading technology insulates, protects and maintains heat in a wide variety of applications. Use our innovative Powerblanket Lite drum/barrel and pail heaters to protect your product from freezing and heat to optimal viscosity.



STANDOUT FEATURES:

- Quickly heat materials to a preset 145°F/ 62.8°C (±10 °F/5 ° C)
- Provides an insulated full-wrap design
- Deliver uniform heat to temperature sensitive products
- Preserve expensive materials without scorching or burning
- Prevent waste by maintaining consistent temperatures
- ETL Certified to UL / CSA / CE safety standards

powerblanket
lite





MAINTENANCE-FREE HEATING

Powerblanket Lite products provide a maintenance free heating solution, which eliminates the headache of maintaining critical temperatures. If stored properly, chemicals and industrial products will last longer and be more effective. In turn, this saves time, hassle, and money.

On those occasions when you don't need all the extra strength and durability, however, there's no use paying for more than you need, right? That's why we created our Powerblanket Lite line. For those jobs that don't necessitate the most robust and sturdy application possible, the Powerblanket Lite line is the best answer.



CERTIFIED TO UL/CSA/CE STANDARDS
CONFORMS TO ANSI/UL STD 499
CERTIFIED TO CAN/CSA C22.2 NO 130
CID2-T4 FOR HAZARDOUS LOCATIONS AVAILABLE

POWERBLANKET LITE TECHNICAL SPECS

Product Category	Model #	Cary Part #	Approx. Product Temperature	Container Dimensions (inch/cm)	Voltage	Wattage (+-5%)	Amps (+-5%)	Weight
5 GALLON / 19 LITER BUCKET	PBL05	19WPHL	145 °F ± 10 °F/62.8 °C ± 5 °C	11.8"D x 15.6"H / 30cmx40cm	120V	120	1.00	1.5
15 GALLON /57 LITER BUCKET	PBL15	19W1HL	145 °F ± 10 °F/62.8 °C ± 5 °C	14.4"D x 26.3"H / 37cmx67cm	120V	180	1.50	2.8
30 GALLON / 114 LITER DRUM	PBL30	19W3HL	145 °F ± 10 °F/62.8 °C ± 5 °C	12.5"Dx24"H / 32cmx61cm	120V	280	2.33	4.1
55 GALLON / 208 LITER DRUM	PBL55	19B4HL	145 °F ± 10 °F/62.8 °C ± 5 °C	23.3"D x 34.9"H / 59cmx89cm	120V	240	2.00	3.1
55 GALLON / 208 LITER DRUM	PBL55F	19B5HL	145 °F ± 10 °F/62.8 °C ± 5 °C	23.3"D x 34.9"H / 59cmx89cm	120V	400	3.33	10.1
1 GALLON/4 LITER PAIL	PBL1G	19W0HL	122 °F ± 10 °F / 50 °C ± 5 °C	6.5"D x 7.5"H / 17cmx19cm	120V	45	0.38	0.6
2 GALLON/8 LITER PAIL	PBL2G	19W2HL	122 °F ± 10 °F / 50 °C ± 5 °C	9.2"D x 9.5" H / 23cmx24cm	120V	45	0.38	0.8

The
CARYCOMPANY
Est. 1895

All Standard AC Products are Certified by ETL to Applicable ANSI/UL/CSA & CE Safety Standards --- cETLus & C E

Additional specifications available including: 240 VAC and Class I Division 2 Groups A through D ; T4

Powerblanket reserves the right to improve products and change specifications without notification *All temperatures may vary based on boundary conditionater that fits your specific needs.